

HRC 100

Basic
Indoor/Outdoor
Controller

controllers

Features

- Available in 4, 6, 9, or 12 stations
- Indoor and outdoor locking enclosure
- Simple programming
- Dedicated master valve/pump start terminal
- Rain delay from 24 hours up to 32 days
- Rain/freeze sensor port
- Wireless rain/freeze sensor port
- 3 programs with 4 start times per program

Specifications

- Transformer:
Input 120VAC or 220/230VAC
Output 24-26VAC 0.6A
- Station output: 24-26VAC 0.25A
- Pump/master valve output:
Max holding 24VAC 0.4A
Max inrush 24VAC 0.6A
- Station timing from 1-240 minutes
- Up to 12 start times per day
- Programming schedule: days of week, watering intervals, and odd/even days
- Water budgeting: adjusts 10% to 200% in 10% increments.

Approvals

- FCC, CSA, CE



CUSTOMIZED CONTROLLERS



Advertise your company, build your brand, and differentiate yourself from your competition with your company name, logo, phone number, and website printed on every HRC 400 and HRC 100 controller you install. See your authorized Hydro-Rain distributor for details and ordering instructions.

How to Specify

	Model
HRC	Controller
	Series
100	Basic
	Type
C	Controller
	Stations
4	4 Station
6	6 Station
9	9 Station
12	12 Station
	Options
L	Custom Logo Imprint

Models (SKU)

- HRC-100-C-04 (04054)
- HRC-100-C-04L (04054P)
- HRC-100-C-06 (04056)
- HRC-100-C-06L (04056P)
- HRC-100-C-09 (04059)
- HRC-100-C-09L (04059P)
- HRC-100-C-12 (04052)
- HRC-100-C-12L (04052P)